

# CLIMENE PRO WALL-MOUNTED

## 64022

Project	
Type	
Notes	
Amount	
Date	

### GENERAL

Protection rating: IP20  
 Protection Class: Class II  
 Housing Color: white  
 RAL: similar to RAL 9016

### LED

Luminous Flux: 2572 lumen  
 Colour temperature: 3000K  
 CRI: >80  
 Lifetime: L70 50.000h

### OPTICS

Optics: Cover PMMA opal  
 Light Emission: direct/indirect

### ELECTRICS

Power: 40 watt  
 Driver: incl. LED driver  
 Dimmability: DALI  
 Voltage: 220-240V 50/60Hz  
 Circuit breaker type B16: 23pcs.


### DIMENSIONS

Length: 1180 mm  
 Width: 15 mm  
 Height: 80 mm  
 Weight: 2.31 kg  
 Mounting depth: 50 mm



CLIMENE PRO Wall-mounted luminaire made of die-cast aluminium; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; direct/indirect light emission; incl. LED driver DALI; light control directly through Cover PMMA opal; System luminous flux of 2572lm at 40W; colour temperature 3000K; CRI >80; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L70 50.000h; protection type IP20; protection class II; dimensions: LxWxH: 1180x15x80mm; depth: 50mm; Weight: 2.31kg

### LIGHT DISTRIBUTION



### DRAWING

