

LINE 48V ROBE 48V TRACK SYSTEM

648RU-309301-OOBLG

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Protection rating: IP20
 Protection Class: Class III
 Housing Color: black
 RAL: similar to RAL 9005
 Decoration ring colour: gold

LED

Luminous Flux: 2273 lumen
 Output: 48Vdc
 Colour temperature: 3000K
 CRI: > 90
 Lifetime: L80 B10 50.000h
 Energy efficiency class: D

OPTICS

Optics: U-Shaped rope light
 Light Emission: direct
 Beam angle: 360°

ELECTRICS

Power: 17.5 watt
 Driver: incl. LED driver
 Dimmability: on/off
 Voltage: 220-240V 50/60Hz

DIMENSIONS

Length: 1260 mm
 Weight: 1.25 kg
 Diameter: ø 30 mm



LINE 48V ROBE U-Shape - Pendant luminaire for 48V low-voltage system made of die-cast aluminum; luminaire with fine-textured matt black powder-coated finish - similar to RAL 9005; golden decoration ring; incl. LED driver on/off; light control directly through U-Shaped rope light; beam characteristic with a beam angle of 360°; System luminous flux of 2273lm at 17.5W; color temperature 3000K; Colour Rendering Index (CRI) > 90; binning initial MacAdam ≤ 3 SDCM; lifetime: L80 B10 50.000h; protection type IP20; protection class III; Dimensions DMxL: ø30mm x 1260mm; Weight: 1.25kg; light source and driver replaceable by a qualified electrician

DRAWING

