

ZIMBA PRO WALL-MOUNTED (RECESSED)

65095

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Protection rating: IP54
 Protection Class: Class I
 Housing Color: white
 RAL: similar to RAL 9016

LED

Luminous Flux: 197 lumen
 Colour temperature: 4000K
 CRI: >80
 Lifetime: L70 50.000h

OPTICS

Optics: cover made of tempered glass
 Light Emission: direct

ELECTRICS

Power: 4.5 watt
 Driver: incl. LED driver
 Dimmability: on/off
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Width: 65 mm
 Weight: 0.35 kg
 Cut out: 96 mm x 96 mm
 Mounting depth: 60 mm
 Dimension: 105 mm x 105 mm



ZIMBA PRO wall-mounted (recessed) luminaire with a narrow mounting frame made of die-cast aluminium; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; direct light emission; incl. LED driver on/off; light control directly through cover made of tempered glass; System luminous flux of 197lm at 4.5W; colour temperature 4000K; CRI >80; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L70 50.000h; protection type IP54; protection class I; dimensions: LxWxH: 105 mm x 105 mm x 65mm; Cut-out: LxWxD: 96 mm x 96 mm x 60 mm; Weight: 0.35kg

LIGHT DISTRIBUTION



DRAWING

