

ZIMBA PRO WALL-MOUNTED (RECESSED)

66267

| | |
|---------|--|
| Project | |
| Type | |
| Notes | |
| Amount | |
| Date | |

GENERAL

Protection rating: IP65
 Protection Class: Class I
 Housing Color: silver
 RAL: similar to RAL 9006

LED

Luminous Flux: 197 lumen
 Colour temperature: 4000K
 CRI: >80
 Lifetime: L70 50.000h

OPTICS

Optics: diffuser of tempered glass
 Light Emission: direct

ELECTRICS

Power: 3 watt
 Driver: incl. LED driver
 Dimmability: on/off
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Width: 65 mm
 Weight: 0.32 kg
 Cut out: 98 mm x 60 mm
 Mounting depth: 60 mm
 Dimension: 108 mm x 76 mm



ZIMBA PRO wall-mounted (recessed) luminaire with a narrow mounting frame made of die-cast aluminium; luminaire with fine-textured matt silver powder-coated finish - similar to RAL 9006; direct light emission; incl. LED driver on/off; light control directly through diffuser of tempered glass; System luminous flux of 197lm at 3W; colour temperature 4000K; CRI >80; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L70 50.000h; protection type IP65; protection class I; dimensions: LxWxH: 108 mm x 76 mm x 65mm; Cut-out: LxWxD: 98 mm x 60 mm x 6 mm; Weight: 0.32kg

LIGHT DISTRIBUTION



DRAWING

