

ZIMBA PRO WALL-MOUNTED (RECESSED)

66269

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Protection rating: IP65
 Protection Class: Class I
 Housing Color: silver
 RAL: similar to RAL 9006

LED

Luminous Flux: 183 lumen
 Colour temperature: 4000K
 CRI: >80
 Lifetime: L70 50.000h

OPTICS

Optics: diffuser of tempered glass
 Light Emission: direct
 Beam angle: 110°

ELECTRICS

Power: 4 watt
 Driver: incl. LED driver
 Dimmability: on/off
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Width: 70 mm
 Weight: 0.47 kg
 Cut out: 153 mm x 58 mm
 Mounting depth: 65 mm
 Dimension: 160 mm x 65 mm



ZIMBA PRO wall-mounted (recessed) luminaire with a narrow mounting frame made of die-cast aluminium; luminaire with fine-textured matt silver powder-coated finish - similar to RAL 9006; direct light emission; incl. LED driver on/off; light control directly through diffuser of tempered glass; System luminous flux of 183lm at 4W; colour temperature 4000K; CRI >80; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L70 50.000h; protection type IP65; protection class I; dimensions: LxWxH: 160 mm x 65 mm x 70mm; Cut-out: LxWxD: 153 mm x 58 mm x 65 mm; Weight: 0.47kg

LIGHT DISTRIBUTION



DRAWING

