

BARISARDA DESK-MOUNTED

68759

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Protection rating: IP20
 Protection Class: Class I
 Housing Color: black
 RAL: similar to RAL 9005

LED

Luminous Flux: 9078 lumen
 Colour temperature: 4000K
 CRI: >80
 Lifetime: L80 50.000h

OPTICS

Optics: Reflector black
 Light Emission: direct/indirect
 Beam angle: 76°

ELECTRICS

Power: 77 watt
 Driver: incl. LED driver
 Dimmability: daylight & motion sensor
 Voltage: 220-240V 50/60Hz
 Circuit breaker type B16: 7pcs.


DIMENSIONS

Length: 1203 mm
 Width: 52 mm
 Height: 1314 mm
 Weight: 4.3 kg



BARISARDA desk-mounted luminaire made of extruded aluminium profile; luminaire with fine-textured matt black powder-coated finish - similar to RAL 9005; direct/indirect light emission; incl. LED driver with three integrated push buttons for direct/indirect together or direct and indirect separately; with integrated daylight & motion sensor; light control directly through Reflector black for lower glaring (UGR<12) ; beam characteristic with a beam angle of 76°; System luminous flux of 9078lm at 77W; colour temperature 4000K; CRI >80; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L80 50.000h; protection type IP20; protection class I; dimensions: LxWxH: 1203mm x 52mm x 1314mm; Weight: 4.3kg; 2500mm power cable with country-specific shock proof CEE 7/7 (Type E+F)

LIGHT DISTRIBUTION



DRAWING

