

LINE40 SURFACE-MOUNTED

LI40A-058401-HDBLO


Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: black
 RAL: similar to RAL 9005
 Protection rating: IP20
 Protection Class: Class I

LED

Luminous Flux: 1439 lumen
 Output: LED high Output
 Colour temperature: 4000K
 CRI: > 80
 Lifetime: L80 B10 50.000h
 Energy efficiency class: C



OPTICS

Light Emission: direct
 Optics: Cover PMMA opal

ELECTRICS


Power: 16.7 watt
 Dimmability: DALI
 Circuit breaker type B16: 28pcs.
 Voltage: 220-240V 50/60Hz

DIMENSIONS

Length: 571 mm
 Width: 41 mm
 Height: 62 mm
 Weight: 1.5 kg

LINE40 Surface-mounted luminaire made of extruded aluminium profile; luminaire with fine-textured matt black powder-coated finish - similar to RAL 9005; direct light emission; through-wiring 5-pole; incl. LED driver DALI; light control directly through Cover PMMA opal; LED high Output option with a System luminous flux of 1439lm at 16.7W; colour temperature 4000K; CRI > 80; Binning initial MacAdam ≤ 3 SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 50.000h; protection type IP20; protection class I; dimensions: LxWxH: 571x41x62mm; Weight: 1.5kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

