

LINE40 SURFACE-MOUNTED

LI40A-088301-HOWHU

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: white
 RAL: similar to RAL 9016
 Protection rating: IP20
 Protection Class: Class I

LED

Luminous Flux: 2148 lumen
 Output: LED high Output
 Colour temperature: 3000K
 CRI: > 80
 Lifetime: L80 B10 50.000h
 Energy efficiency class: D

OPTICS


Light Emission: direct
 Optics: Cover PMMA opal U

ELECTRICS

Power: 23.3 watt
 Dimmability: on/off
 Circuit breaker type B16: 22pcs.
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Length: 851 mm
 Width: 41 mm
 Height: 83 mm
 Weight: 2 kg



LINE40 Surface-mounted luminaire made of extruded aluminium profile; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; direct light emission; through-wiring 5-pole; incl. LED driver on/off; light control directly through Cover PMMA opal U; LED high Output option with a System luminous flux of 2148lm at 23.3W; colour temperature 3000K; CRI > 80; Binning initial MacAdam ≤ 3 SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 50.000h; protection type IP20; protection class I; dimensions: LxWxH: 851x41x83mm; Weight: 2kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

