

# LINE40 SURFACE-MOUNTED

## LI40A-148401-HOSIM

Project	
Type	
Notes	
Amount	
Date	

### GENERAL

Housing Color: silver  
 RAL: similar to RAL 9006  
 Protection rating: IP20  
 Protection Class: Class I

### LED

Luminous Flux: 3757 lumen  
 Output: LED high Output  
 Colour temperature: 4000K  
 CRI: > 80  
 Lifetime: L80 B10 50.000h  
 Energy efficiency class: C

### OPTICS

Light Emission: direct  
 Optics: Cover PMMA microprism

### ELECTRICS

Power: 35.1 watt  
 Dimmability: on/off  
 Circuit breaker type B16: 22pcs.  
 Voltage: 220-240V 50/60Hz


### DIMENSIONS

Length: 1411 mm  
 Width: 41 mm  
 Height: 62 mm  
 Weight: 3.5 kg



LINE40 Surface-mounted luminaire made of extruded aluminium profile; luminaire with fine-textured matt silver powder-coated finish - similar to RAL 9006; direct light emission; through-wiring 5-pole; incl. LED driver on/off; light control directly through Cover PMMA microprism; LED high Output option with a System luminous flux of 3757lm at 35.1W; colour temperature 4000K; CRI > 80; Binning initial MacAdam  $\leq 3$  SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 50.000h; protection type IP20; protection class I; dimensions: LxWxH: 1411x41x62mm; Weight: 3.5kg; light source and driver replaceable by a qualified electrician

### LIGHT DISTRIBUTION



### DRAWING

