

LINE50 RECESSED-MOUNTED FRAME

LI50E-319301-HDBLA

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: black
 RAL: similar to RAL 9005
 Protection rating: IP20
 Protection Class: Class I

LED

Luminous Flux: 7550 lumen
 Output: LED high Output
 Colour temperature: 3000K
 CRI: > 90
 Lifetime: L80 B10 50.000h
 Energy efficiency class: D

OPTICS

Light Emission: direct
 Optics: Cover PMMA asymmetric

ELECTRICS

Power: 75.5 watt
 Dimmability: DALI
 Circuit breaker type B16: 28pcs.
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Length: 3141 mm
 Width: 63 mm
 Height: 77 mm
 Weight: 7.5 kg



LINE50 Recessed-mounted frame luminaire with a narrow mounting frame made of extruded aluminium profile; luminaire with fine-textured matt black powder-coated finish - similar to RAL 9005; direct light emission; through-wiring 5-pole; incl. LED driver DALI; light control directly through Cover PMMA asymmetric; LED high Output option with a System luminous flux of 7550lm at 75.5W; colour temperature 3000K; CRI > 90; Binning initial MacAdam ≤ 3 SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 50.000h; protection type IP20; protection class I; dimensions: LxWxH: 3141x63x77mm; Cut-out: L: 3136 mm, WxD: 57x125mm; Weight: 7.5kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

