

# LINE50 WALL-MOUNTED

## LI50W-198301-LOWHM

Project	
Type	
Notes	
Amount	
Date	

### GENERAL

Housing Color: white  
 RAL: similar to RAL 9016  
 Protection rating: IP20  
 Protection Class: Class I

### LED

Luminous Flux: 2536 lumen  
 Output: LED low Output  
 Colour temperature: 3000K  
 CRI: > 80  
 Lifetime: L80 B10 50.000h  
 Energy efficiency class: C

### OPTICS

Light Emission: direct  
 Optics: Cover PMMA microprism

### ELECTRICS

Power: 23.7 watt  
 Dimmability: on/off  
 Circuit breaker type B16: 16pcs.  
 Voltage: 220-240V 50/60Hz


### DIMENSIONS

Length: 1932 mm  
 Width: 50 mm  
 Height: 80.5 mm  
 Weight: 4.6 kg



LINE50 Wall-mounted luminaire made of extruded aluminium profile; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; direct light emission; through-wiring 5-pole; incl. LED driver on/off; light control directly through Cover PMMA microprism; incl. special quick-mount wall canopy (mounting with male and female plug system); LED low Output option with a System luminous flux of 2536lm at 23.7W; colour temperature 3000K; CRI > 80; Binning initial MacAdam ≤ 3 SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 50.000h; protection type IP20; protection class I; dimensions: LxWxH: 1932x50x80.5mm; Weight: 4.6kg; light source and driver replaceable by a qualified electrician

### LIGHT DISTRIBUTION



### DRAWING

