

# OFFICELINE50 SUSPENDED LUMINAIRE

## OL50H-149401-HOSIT

Project	
Type	
Notes	
Amount	
Date	

### GENERAL

Housing Color: silver  
 RAL: similar to RAL 9006  
 Protection rating: IP20  
 Protection Class: Class I

### LED

Luminous Flux: 4465 lumen  
 Output: LED high Output  
 Colour temperature: 4000K  
 Lifetime: L80 B10 50.000h  
 Energy efficiency class: D

### OPTICS

Optics: BAP-Louvre titan specular

### ELECTRICS

Power: 46 watt  
 Driver: incl. LED driver  
 Dimmability: on/off  
 Circuit breaker type B16: 21pcs.


### DIMENSIONS

Length: 1449 mm  
 Width: 50 mm  
 Height: 80.5 mm  
 Weight: 3.7 kg



officeLINE50 Suspended luminaire luminaire made of extruded aluminium profile; luminaire with fine-textured matt silver powder-coated finish - similar to RAL 9006; direct light emission; through-wiring 5-pole; incl. LED driver on/off; light control directly through special faceted BAP-Louvre titan specular for lower glaring (UGR<19) ; incl. white canopy with transparent power feed cable as well as flexibly positionable suspension cable hangers (2000mm) and quick-release clamps for infinitely variable adjustment of the mounting height; LED high Output option with a System luminous flux of 4465lm at 46W; colour temperature 4000K; CRI > 90; Binning initial MacAdam ≤ 3 SDCM; retinal blue light hazard according to IEC TR 62778 risk group RG 1 (unlimited) - no risk; Lifetime: L80 B10 50.000h; protection type IP20; protection class I; dimensions: LxWxH: 1449x50x80.5mm; Weight: 3.7kg; light source and driver replaceable by a qualified electrician

### LIGHT DISTRIBUTION



### DRAWING

