

Project	
Type	
Notes	
Amount	
Date	

ROUND90 SURFACE-MOUNTED

RO90A-659272-HDWGM

GENERAL

Housing Color: white
 RAL: similar to RAL 9016
 Protection rating: IP50
 Protection Class: Class I

LED

Luminous Flux: 6149 lumen
 Output: LED high Output
 Colour temperature: 2700K
 CRI: > 90
 Lifetime: L80 B10 50.000h
 Energy efficiency class: D

OPTICS

Light Emission: direct/indirect
 Optics: Cover PMMA microprism

ELECTRICS

Power: 51.3 watt
 Driver: incl. LED driver
 Dimmability: DALI
 Circuit breaker type B16: 18pcs.
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Diameter: \varnothing 650 mm
 Height: 90 mm
 Weight: 7.6 kg



ROUND90 round Surface-mounted made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; decoration ring colour: beaten gold; direct/indirect light emission; incl. LED driver DALI; light control directly through Cover PMMA microprism; LED high Output option with a System luminous flux of 6149lm at 51.3W; colour temperature 2700K; CRI > 90; installation by innovative "slide & light" principle; Binning initial MacAdam \leq 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; Dimension: DMxH: 650x90mm; Weight: 7.6kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

