

ROUND90 SUSPENDED LUMINAIRE

RO90R-358401-HOBBB

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: black
 RAL: similar to RAL 9005
 Protection rating: IP50
 Protection Class: Class I

LED

Luminous Flux: 1667 lumen
 Output: LED high Output
 Colour temperature: 4000K
 CRI: > 80
 Lifetime: L80 B10 50.000h
 Energy efficiency class: B

OPTICS

Light Emission: direct
 Optics: Cover PMMA office special

ELECTRICS

Power: 12.9 watt
 Driver: incl. LED driver
 Dimmability: on/off
 Circuit breaker type B16: 40pcs.
 Voltage: 220-240V 50/60Hz

DIMENSIONS

Diameter: \varnothing 350 mm
 Height: 90 mm
 Weight: 3.4 kg



ROUND90 round Suspended luminaire with rod suspension "R" and luminaire housing made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt black powder-coated finish - similar to RAL 9005; decoration ring colour: black; direct light emission; incl. LED driver on/off; light control directly through Cover PMMA office special; LED high Output option with a System luminous flux of 1667lm at 12.9W; colour temperature 4000K; CRI > 80; incl. 1000mm pendant tube (can be shortened) and canopy in housing color; Binning initial MacAdam \leq 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; dimensions: DMxH: 350x90mm; Weight: 3.4kg; light source and driver replaceable by a qualified electrician

DRAWING

