

ROUND90 SUSPENDED LUMINAIRE

RO90R-659301-LOSGM

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: silver
 RAL: similar to RAL 9006
 Protection rating: IP50
 Protection Class: Class I

LED

Luminous Flux: 2934 lumen
 Output: LED low Output
 Colour temperature: 3000K
 CRI: > 90
 Lifetime: L80 B10 50.000h
 Energy efficiency class: D

OPTICS

Light Emission: direct
 Optics: Cover PMMA microprism

ELECTRICS

Power: 27.2 watt
 Driver: incl. LED driver
 Dimmability: on/off
 Circuit breaker type B16: 17pcs.
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Diameter: \varnothing 650 mm
 Height: 90 mm
 Weight: 7.6 kg



ROUND90 round Suspended luminaire with rod suspension "R" and luminaire housing made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt silver powder-coated finish - similar to RAL 9006; decoration ring colour: beaten gold; direct light emission; incl. LED driver on/off; light control directly through Cover PMMA microprism; LED low Output option with a System luminous flux of 2934lm at 27.2W; colour temperature 3000K; CRI > 90; incl. 1000mm pendant tube (can be shortened) and canopy in housing color; Binning initial MacAdam \leq 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; dimensions: DMxH: 650x90mm; Weight: 7.6kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

