

ROUND90 WALL-MOUNTED

RO90W-358402-LDSGB

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Housing Color: silver
 RAL: similar to RAL 9006
 Protection rating: IP50
 Protection Class: Class I

LED

Luminous Flux: 1687 lumen
 Output: LED low Output
 Colour temperature: 4000K
 CRI: > 80
 Lifetime: L80 B10 50.000h
 Energy efficiency class: B

OPTICS


Light Emission: direct/indirect
 Optics: Cover PMMA office special

ELECTRICS

Power: 11.9 watt
 Driver: incl. LED driver
 Dimmability: DALI
 Circuit breaker type B16: 40pcs.
 Voltage: 220-240V 50/60Hz


DIMENSIONS

Diameter: \varnothing 350 mm
 Height: 90 mm
 Weight: 3.4 kg



ROUND90 round Wall-mounted made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt silver powder-coated finish - similar to RAL 9006; decoration ring colour: beaten gold; direct/indirect light emission; incl. LED driver DALI; light control directly through Cover PMMA office special; LED low Output option with a System luminous flux of 1687lm at 11.9W; colour temperature 4000K; CRI > 80; installation by innovative "slide & light" principle; Binning initial MacAdam \leq 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; dimensions: DMxH: 350x90mm; Weight: 3.4kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

