

SQUARE90 WALL-MOUNTED

SQ90W-659272-HDBBO

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Protection rating: IP50
 Protection Class: Class I
 Housing Color: black
 RAL: similar to RAL 9005
 Decorationring colour: black

LED

Luminous Flux: 7372 lumen
 Output: LED high Output
 Colour temperature: 2700K
 CRI: > 90
 Lifetime: L80 B10 50.000h
 Energy efficiency class: D

OPTICS

Optics: Cover PMMA opal
 Light Emission: direct/indirect

ELECTRICS

Power: 61.8 watt
 Driver: incl. LED driver
 Dimmability: DALI
 Voltage: 220-240V 50/60Hz
 Circuit breaker type B16: 13pcs.


DIMENSIONS

Length: 650 mm
 Width: 650 mm
 Height: 90 mm
 Weight: 9.3 kg



SQUARE90 square Wall-mounted made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt black powder-coated finish - similar to RAL 9005; decoration ring colour: black; direct/indirect light emission; incl. LED driver DALI; light control directly through Cover PMMA opal; LED high Output option with a System luminous flux of 7372lm at 61.8W; colour temperature 2700K; CRI > 90; installation by innovative "slide & light" principle; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; Dimensions: LxWxH: 650x650x90mm; Weight: 9.3kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

