

SQUARE90 WALL-MOUNTED

SQ90W-659301-LDSSM

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Protection rating: IP50
 Protection Class: Class I
 Housing Color: silver
 RAL: similar to RAL 9006
 Decorationring colour: silver

LED

Luminous Flux: 3421 lumen
 Output: LED low Output
 Colour temperature: 3000K
 CRI: > 90
 Lifetime: L80 B10 50.000h
 Energy efficiency class: D

OPTICS

Optics: Cover PMMA microprism
 Light Emission: direct

ELECTRICS

Power: 30.5 watt
 Driver: incl. LED driver
 Dimmability: DALI
 Voltage: 220-240V 50/60Hz
 Circuit breaker type B16: 18pcs.


DIMENSIONS

Length: 650 mm
 Width: 650 mm
 Height: 90 mm
 Weight: 9.3 kg



SQUARE90 square Wall-mounted made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt silver powder-coated finish - similar to RAL 9006; decoration ring colour: silver; direct light emission; incl. LED driver DALI; light control directly through Cover PMMA microprism; LED low Output option with a System luminous flux of 3421lm at 30.5W; colour temperature 3000K; CRI > 90; installation by innovative "slide & light" principle; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; Dimensions: LxWxH: 650x650x90mm; Weight: 9.3kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

