

# SQUARE90 WALL-MOUNTED

## SQ90W-659301-LDWGM

Project	
Type	
Notes	
Amount	
Date	

### GENERAL

Protection rating: IP50  
 Protection Class: Class I  
 Housing Color: white  
 RAL: similar to RAL 9016  
 Decorationring colour: beaten gold

### LED

Luminous Flux: 3504 lumen  
 Output: LED low Output  
 Colour temperature: 3000K  
 CRI: > 90  
 Lifetime: L80 B10 50.000h  
 Energy efficiency class: D

### OPTICS

Optics: Cover PMMA microprism  
 Light Emission: direct

### ELECTRICS

Power: 30.5 watt  
 Driver: incl. LED driver  
 Dimmability: DALI  
 Voltage: 220-240V 50/60Hz  
 Circuit breaker type B16: 18pcs.


### DIMENSIONS

Length: 650 mm  
 Width: 650 mm  
 Height: 90 mm  
 Weight: 9.3 kg



SQUARE90 square Wall-mounted made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; decoration ring colour: beaten gold; direct light emission; incl. LED driver DALI; light control directly through Cover PMMA microprism; LED low Output option with a System luminous flux of 3504lm at 30.5W; colour temperature 3000K; CRI > 90; installation by innovative "slide & light" principle; Binning initial MacAdam  $\leq 3$  SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; Dimensions: LxWxH: 650x650x90mm; Weight: 9.3kg; light source and driver replaceable by a qualified electrician

### LIGHT DISTRIBUTION



### DRAWING

