

SQUARE90 WALL-MOUNTED

SQ90W-958301-HDWAB

Project	
Type	
Notes	
Amount	
Date	

GENERAL

Protection rating: IP50
 Protection Class: Class I
 Housing Color: white
 RAL: similar to RAL 9016
 Decorationring colour: beaten silver

LED

Luminous Flux: 16803 lumen
 Output: LED high Output
 Colour temperature: 3000K
 CRI: > 80
 Lifetime: L80 B10 50.000h
 Energy efficiency class: C

OPTICS

Optics: Cover PMMA office special
 Light Emission: direct

ELECTRICS

Power: 102.8 watt
 Driver: incl. LED driver
 Dimmability: DALI
 Voltage: 220-240V 50/60Hz
 Circuit breaker type B16: 13pcs.


DIMENSIONS

Length: 950 mm
 Width: 950 mm
 Height: 90 mm
 Weight: 23.4 kg



SQUARE90 square Wall-mounted made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; decoration ring colour: beaten silver; direct light emission; incl. LED driver DALI; light control directly through Cover PMMA office special; LED high Output option with a System luminous flux of 16803lm at 102.8W; colour temperature 3000K; CRI > 80; installation by innovative "slide & light" principle; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; Dimensions: LxWxH: 950x950x90mm; Weight: 23.4kg; light source and driver replaceable by a qualified electrician

LIGHT DISTRIBUTION



DRAWING

