

# SQUARE90 WALL-MOUNTED

## SQ90W-959271-LDWBB

Project	
Type	
Notes	
Amount	
Date	

### GENERAL

Protection rating: IP50  
 Protection Class: Class I  
 Housing Color: white  
 RAL: similar to RAL 9016  
 Decorationring colour: black

### LED

Luminous Flux: 8041 lumen  
 Output: LED low Output  
 Colour temperature: 2700K  
 CRI: > 90  
 Lifetime: L80 B10 50.000h  
 Energy efficiency class: D

### OPTICS


Optics: Cover PMMA office special  
 Light Emission: direct

### ELECTRICS

Power: 60.9 watt  
 Driver: incl. LED driver  
 Dimmability: DALI  
 Voltage: 220-240V 50/60Hz  
 Circuit breaker type B16: 18pcs.


### DIMENSIONS

Length: 950 mm  
 Width: 950 mm  
 Height: 90 mm  
 Weight: 23.4 kg



SQUARE90 square Wall-mounted made of aluminium profile rolled seamlessly welded; luminaire with fine-textured matt white powder-coated finish - similar to RAL 9016; decoration ring colour: black; direct light emission; incl. LED driver DALI; light control directly through Cover PMMA office special; LED low Output option with a System luminous flux of 8041lm at 60.9W; colour temperature 2700K; CRI > 90; installation by innovative "slide & light" principle; Binning initial MacAdam ≤ 3 SDCM; Lifetime: L80 B10 50.000h; protection rating IP50; protection class I; Dimensions: LxWxH: 950x950x90mm; Weight: 23.4kg; light source and driver replaceable by a qualified electrician

### LIGHT DISTRIBUTION



### DRAWING

